MAGNETIC SIGN USE AND CARE INSTRUCTIONS

- When not in use magnetics must be kept flat or store rolled standing on end to prevent flat spots. Store rolled magnetics print side out.
- Apply magnetics to clean dry surface. Allow waxes to completely cure for 2 days before application.
- For best results apply when magnetic material is 60 degrees or above.
- Allow 60-90 days for fresh paint to cure before applying magnetics.
- Applying magnetics: Affix to smooth or gently curved surfaces only. Do not apply over concave areas, body molding, pin striping, decals, etc. NO air pockets.
- If placed in the wrong position completely remove the magnetic and reaffix. Do not pull the magnetic across the surface as it may scratch the surface and damage the magnetic.
- To prevent dirt and moisture build up between the magnetic and the surface, clean both the magnetic and the surface with a mild detergent, wipe dry with a soft cloth and allow to completely dry.
- Magnetics applied to Vehicles Remove and Clean DAILY.
- Long-term use on vehicles can result in uneven fading because the area covered by the magnetic is shielded from the sun.
- Radius Corners are recommended for use on vehicles.

THERE IS NO WARRANTY EXPRESSED OR IMPLIED AGAINST LOSS OF SIGNS OR DAMAGE TO VEHICLE SURFACES. JACK RABBIT SIGN SHOP IS NOT LIABLE FOR THE CARE, ALTERATION, STORAGE, AND/OR USE OF THE MAGNETS, OR THE SURFACE TO WHICH THE MAGNETS ARE APPLIED.

